



Declaration of Performance

DoP-No.: 4026639011947-007314

① **DA**

② 10098

(batch number see imprint on membrane)

Vapour check and airtightness membrane

④ MOLL bauökologische Produkte GmbH
Rheintalstraße 35 - 43
68723 Schwetzingen

System 3

The notified body "MPA Dresden GmbH" - NB 0767 - carried out the initial tests of the material properties according to system 3.

⑨ Performance declared according to BS EN 13984 - Typ A

Attribute	Norm	Value
Length ¹		50 m
Width ²		1.5 m
Surface weight	BS EN 1849-2:2001	130 ±5 g/m ²
Thickness	BS EN 1849-2:2001	0.45 ±0.05 mm
sd-value	BS EN 1931:2001	11.5 ±1.25 MNs/g
Fire behaviour	BS EN 13501-1	E
Water resistance	BS EN 1928:2000	W1
Tensile strength MD/CD	BS EN 12311-2:1999	230 N/5 cm / 200 N/5 cm
Elongation MD/CD	BS EN 12311-2:1999	90 % / 90 %
Nail tear resistance MD/CD	BS EN 12310-1:1999	120 N / 115 N
Artificial ageing by long term	BS EN 1296 :2001 / BS EN 1931:2001	passed

dimensional tolerances: ¹: +0.5 m; ²: +0.005 m

The performance of the product according to numbers 1 and 2 correspond to the performance declared according to number 9. According to number 4, the manufacturer is solely responsible for issuing this Declaration of Performance. Signed for the manufacturer and on behalf of the manufacturer by:

Lothar Moll, CEO

Michael Förster, technical manager
Schwetzingen, 08/26/2014